



ineo+ 3320i

- Colour A4 multifunctional
- > Up to 33 ppm

Option diagram















Finishing functionalities





Duplex



stapling (offline)

Description

Bitdefender® Antivirus provides real time scanning
of all incoming and outgoing data
Super G3 fax; digital fax functionality
Wireless LAN and wireless LAN Access Point Mode
USB keyboard connection
USB keyboard connection; Bluetooth
To connect with Android mobile devices
GPRS modem connection for CSRC
Finger vein scanner
Various ID card technologies
Installation kit for ID card reader

Others	
WT-P03 Working table	Authentication device placement
KP-P03 10-Key pad	For use instead of touchscreen
KH-P02 Keyboard holder	To place USB keyboard
CU-202 Air cleaning unit	Improving indoor air quality by reduced emissions
MK-P09 Mount kit	Installation kit for Air cleaning unit
Media Input PF-P20 Paper tray	500 sheets, A4, 60-90 g/m ²
PF-P22 Height adjustment unit	To achieve comfortable height for operation
DK-P04x Copier desk	Provides storage space for print media and other
	materials
Media output	
FS-P04 Off-line stapler	20-sheet off-line stapling

Technical specifications

SYSTEM SPECIFICATIONS

Panel size/resolution	7" / 800 x 480		
System memory (standard/max	()4,096 MB		
System hard drive	16 GB (standard)		
Interface	10/100/1,000-Base-T Ethernet; USB 2.0;		
	Wi-Fi 802.11 b/g/n (optional)		
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP;		
	HTTP(S); AppleTalk; Bonjour		
Automatic document feeder	Up to 80 originals; A6-A4; 50-128 g/m²;		
(standard)	Dualscan ADF		
Paper input capacity	600 sheets / 1,100 sheets		
(standard/max)			
Paper tray input (standard)	1x 500 sheets; A6–A4; custom sizes; 60–210 g/m²		
Paper tray input (optional)	1x 500 sheets; A4; 60–90 g/m²		
Manual bypass	100 sheets; A6–A4; custom sizes; 60–210 g/m²		
Automatic duplexing	A4; 60-210 g/m²		
Finishing modes (optional)	Group; Sort; Staple (offline)		
Output capacity (standard)	Max. 250 sheets		
Copy/print volume (monthly)	Rec. 6,500 pages; Max. 196,000 pages		
Toner lifetime	Black up to 13,000 pages		
	CMY up to 9,000 pages		
Imaging unit lifetime	Black up to 155,000 pages (imaging unit)		
	CMY up to 55,000 pages (imaging unit)		
Power consumption	220-240 V / 50/60 Hz; Less than 1.45 kW		
System dimension (W x D x H)	420 x 528 x 572 mm (without options)		
System weight	Approx. 38.4 kg (without options)		

PRINTER SPECIFICATIONS

Print resolution	1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi
Page description language	PCL 6 (XL3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Operating System	Windows 7 (32/64); Windows 8/8.1 (32/64);
	Windows 10 (32/64); Windows Server 2008 (32/64);
	Windows Server 2008 R2; Windows Server 2012;
	Windows Server 2012 R2; Windows Server 2016;
	Windows Server 2019; Macintosh OS X 10.10 or later;
	Unix; Linux; Citrix
Printer fonts	80 PCL Latin; 137 PostScript 3 Emulation Latin
Mobile printing	AirPrint (iOS); Mopria (Android)
	Optional: WiFi Direct

SCANNER SPECIFICATIONS

- 1/ / 1	
Scan speed (mono/colour)	Up to 28/28 ipm in simplex
	Up to 56/56 ipm in duplex
Scan modes	Scan-to-eMail (Scan-to-Me);
	Scan-to-SMB (Scan-to-Home); Scan-to-FTP;
	Scan-to-USB; Scan-to-WebDAV; Scan-to-URL
File formats	JPEG; TIFF; PDF; Compact PDF; Encrypted PDF;
	XPS; Compact XPS; PPTX
Scan destinations	2,100 (single + group); LDAP support

COPIER SPECIFICATIONS

Imaging technology	Laser
Toner technology	HD polymerised toner
Copy/print speed A4	Up to 33/33 ppm
(mono/colour)	
Autoduplex speed A4	Up to 33/33 ppm
(mono/colour)	
1st copy out time A4	6.0/7.2 sec.
Warm-up time	Approx. 13 sec. in mono; 15 sec. in color ²
Copy resolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–9,999
Original format	A6–A4; Custom sizes
Magnification	25–400% in 0.1% steps; Auto-zooming

FAX SPECIFICATIONS

Fax standard	Super G3 (optional)
Fax transmission	Analogue; i-Fax; Colour i-Fax; IP-Fax
Fax resolution	Up to 600 x 600 dpi
Fax compression	MH; MR; MMR; JBIG
Fax modem	Up to 33.6 Kbps
Fax destinations	2,100 (single + group)

SYSTEM FEATURES

Security Functions (standard)	IP filtering and port blocking; SSL2; SSL3 and
	TLS1.0/1.1/1.2 network communication;
	IPsec support; IEEE 802.1x support; User authenti-
	cation; Authentication log; Secure print; Kerberos;
	Hard drive data encryption (AES 256)
Security Functions (optional)	Antivirus realtime scanning (Bitdefender®)
Accounting (standard)	Up to 100 user accounts; Active Directory support
	(user name + password + e-mail + smb folder);
	User function access definition
Accounting Functions (optional)	Biometric authentication (finger vein scanner);
	ID card authentication (ID card reader);
	Authentication by mobile device (Android/iOS)
Software	store+find (opt.); convert+share (opt.);
	Device Manager; Box Operator; Data Administrato
	(user accounts & cost centres); Card solutions
	(opt.); EveryonePrint (opt.)

 $^{^{\}mbox{\scriptsize 1}}$ If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

























DEVELOP

Konica Minolta Business Solutions Europe GmbH

Europaallee 17 30855 Langenhagen Germany Phone +49 511 7404-0 www.develop.eu

- All specifications refer to A4-size paper of 80 g/m² quality.
- All specifications refer to A4-size paper of 80 g/m² quality.

 The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.

 The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage of A4). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity.

 Specifications and accessories are based on the information available at the time of printing and are
- -Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- DEVELOP and ineo are registered trademarks/product titles owned by Konica Minolta Business Solutions Europe GmbH.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.

 All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

² Warm-up time may vary depending on the operating environment and usage