

# ineo+1060(L)/1070



- > Colour SRA3+ digital press
- > Up to 3,907 pph

### Features that make all the difference!

In a world of excessive information and ultra-fast communications colour is all the more important because it catches the eye. That can make all the difference between a document being thrown away and getting read. Because brilliant colour improves the communicative power and readability of any document, Develop offers a true innovation in production printing — the ineo+ 1060/1060L/1070.

### Durable performance

### ineo+ 1060/1060L

- Up to 60 A4 pages per minute
- Up to 31 SRA3 pages per minute
- Up to 3,316 A4 pages per hour
- Up to 1,681 SRA3 pages per hour

### ineo+ 1070

- Up to 71 A4 pages per minute
- Up to 36 SRA3 pages per minute
- Up to 3,907 A4 pages per hour
- Up to 1,976 SRA3 pages per hour

### Highest reliability

- Long-life platform, long-lasting parts and consumables
- Registration-swing mechanism for accurate duplex registration
- Fusing-rolling mechanism
- For prints with maximum efficiency



# Ready-made print products

- 50-sheet booklet making with front trimming and 35-sheet booklets with optional creasing, slitting and spine corner forming
- 102 sheets auto ring binding
- · Perfect binding for books of up to 30 mm
- 100-sheet stapling with cutting mechanism
- For highest automation and enormous productivity
- For more profit in the print room

# Geared-up finishing

- Multi (GBC) punching and 2- & 4-hole punching
- · 6 different types of folding
- Large stacking
- Minimised human interaction
- · For optimised budgets

## High-end print control

- Flexible choice of controller technology:
- EFI®, CREO® or proprietary ineo controller
- Integration into hybrid workflows
- · For intuitive operation
- · To save time and money



- (equivalent to 1,200 x 3,600 dpi)
- HD E toner technology
- · Image density control technology
- For new print applications
- For growing business





### Ease of use

- · Automated real-time engine calibration
- · Simple paper catalogue settings
- Operator Replaceable Unit Management (ORUM)
- · For maximum ease of operation
- · Frees operators for other jobs

# Sophisticated media handling

- · Air-suction or air-assist feeding technology
- Up to 7,500 sheets paper input capacity
- Up to 5 paper input trays
- For enhanced overall productivity
- For extreme cost savings

# Comprehensive media processing

- Up to 300 g/m² paper weight in simplex and duplex printing
- Envelope printing support
- Reliable thin paper feeding through air blow fusing separation
- Mechanical decurling
- Optional inter-cooler curl eliminator
- · For highly flexible print products
- To stand out from the competition

### **Environmental** awareness

- Reduced power consumption with HD E toner
- · Increased usage rate of recycled
- PC/ABS materials for reduction of CO₂ emissions
- For reduced environmental impact
- · Improved efficiency based on green values

### **Technical specifications**

### SYSTEM SPECIFICATIONS

Resolution	1,200 x 1,200 dpi x 8 bit
	1,200 x 3,600 dpi equivalent
Paper weight	62-300 g/m²
Duplex unit	Non-stack type; 62–300 g/m²
Paper sizes	330 x 487 mm
Maximum image area	323 x 480 mm
Paper input capacity	Standard: 1,500 sheets
	max.: 7,500 sheets
Paper output capacity	max.: 13,600 sheets
Main unit dimensions	760 x 903 x 1,073 mm
(W x D x H)	
Main unit weight	291 kg
	286 kg (ineo+ 1070L)

### **PRODUCTIVITY**

ineo+ 1070/1070L	
A4 – max. per minute	71 ppm
A3 – max. per minute	38 ppm
SRA3 – max. per minute	36 ppm
A4 – max. per hour	3,907 pph
A3 – max. per hour	2,107 pph
SRA3 – max. per hour	1,976pph
ineo+ 1060	
A4 – max. per minute	60 ppm
A3 – max. per minute	33 ppm
SRA3 – max. per minute	31 ppm
A4 – max. per hour	3,316 pph
A3 – max. per hour	1,792 pph
SRA3 – max. per hour	1,681 pph

#### CONTROLLER

Internal EFI® Fiery Controller	IC-415
External EFI® Fiery Controller	IC-308
External CREO® Controller	IC-309
Internal ineo Controller	IC-602

### SCANNER SPECIFICATIONS\*

Scan speed A4	up to 70 ppm
Scan resolution	600 x 600 dpi
Scan modes	TWAIN scan; Scan-to-HDD; Scan-to-FTP;
	Scan-to-SMB; Scan-to-E-mail
Scan formats	TIFF (single and multi page); PDF

### COPIER SPECIFICATIONS\*

Gradations	256 gradations
FCOT	Less than 8 sec. (colour A4)
Magnification	25-400%; in 0.1% steps
Multiple copies	1-9,999


#### **ACCESSORIES**

Original cover	OC-509*
Automatic document feeder	DF-626*
Working table	WT-511
Heating unit	HT-511
for main body trays	
Air assist paper feed unit	PF-602
Heating unit for PF-602	HT-504
Air suction paper feed unit	PF-707
Heating unit for PF-707	HT-506
Relay unit	RU-509
Humidification unit	HM-102
Multi (GBC) punching unit	GP-501
Relay unit	RU-510
Auto ring binding unit	GP-502
Folding and punching unit	FD-503
Stacking unit	LS-505
Booklet making unit	SD-506
Booklet making unit	SD-513
Creasing unit for SD-513	CR-101
Slitting unit for SD-513	TU-504
Spine corner forming unit	FD-504
for SD-513	
Perfect binding unit	PB-503
Stapling unit	FS-532
Saddle stitch kit for FS-532	SD-510
Punch kit for FS-532	PK-522
Post inserter for FS-532	PI-502
Envelope fuser	EF-103

<sup>\*</sup> Not for ineo 1070L



Konica Minolta Business Solutions Europe GmbH
Europaallee 17 30855 Langenhagen Germany Phone +49 511 7404-0 www.develop.eu



All data relating to the paper capacities of the document feeder, the final processing accessories and the paper cassettes apply to paper weighing 80 g/m² unless expressly stated otherwise. All data relating to the speed of printing, scanning or faxing apply to paper of an A4 format weighing 80 g/m² unless expressly stated otherwise.

All data relating to paper weights apply to media that are recommended by Konica Minolta. All technical data correspond to knowledge available at the time of going to print. Konica Minolta reserves the right to make technical alterations.

DEVELOP and ineo are registered trademarks/product titles owned by Konica Minolta Business Solutions Europe GmbH.

All other brand or product names are registered trademarks or product titles of their respective manufacturers. Konica Minolta does not accept any liability or guarantee for these products.